



### 1987-93 Mustang 5.0 Resto A/C Vent Registers

# Removal

1. Remove all of the existing vent registers and surrounds from the dash.

2. Using a pry tool against the airflow adjustment wheel, carefully pry the vent from the dash until it is fully released. Repeat this for the other vents.

3. To remove the vent surrounds, use a small pry tool and/or pick to release all (4) of the tabs. There are (2) tabs on top and (2) tabs on the bottom.

4. Release (1) tab at a time until all of them are fully released. Repeat this for the remaining surrounds.

## **Painting process**

1. If you are painting these to match your interior, you'll need to remove the vent registers from the surrounds.

(These steps are the same as the removal process.)

2. Scuff everything using a grey scuff pad and some warm water with dish soap.

3. Wipe the residue with a plastic safe wax and grease remover to further remove any contaminants from the surface.

4. Work in a well-lit and well-ventilated area. Hang the parts and begin painting.

5. Apply light coats at first and then finish off with a medium coat. Be sure to use overlapping passes, and hold the can about 6-10 inches from the surface.

6. Allow adequate time to dry before handling.











FIND YOUR NEXT MOD! SHOP 1000s OF PARTS ONLINE 24/7@LMR.C

Copyright © 2020 LMR All rights reserved. No part of this publication may be reproduced, distributed, or transmitted in any form or by any means.

### **Reassembly & Installation**

1. Once the pieces are dry, repaint the indicator markers. These include the center notch in the dial and the open and closed indicators.

This is done using some enamel model paint and a small paintbrush.

2. Install the new surrounds into the dash.

3. When doing this, verify that all of the upper and lower retaining tabs fully seat.

4. You can use a small pry tool to ensure these are seated against the dash.

(Fitment Note) If you've installed an aftermarket dash pad, you may have to clearance the backside of the pad in order for the tabs on the vent surrounds to fully engage. This is because of the variances in pad thickness on aftermarket dash pads.

5. Once all of the surrounds are installed, position each of the vent registers into place.

6. Insert these as straight as possible into the surround until you hear them 'click'.

7. Repeat this for the remaining vent registers.

8. Verify the functionality of each vent and you're all done.











### Disclaimer

By using this instruction sheet, you agree that other than as expressly stated in the LMR Terms and Conditions (Agreement) or as required by the laws of the state of Texas or applicable United States federal law (Applicable Law), this instruction sheet is provided "AS IS" and LMR does not make any specific representations or warranties about this instruction sheet. For example, LMR does not make any warranties about: (a) the content provided in this instruction sheet; (b) any specific features of this instruction sheet, or its accuracy, reliability, or ability to meet your needs. The knowledge and experience level of users of this instruction sheet vary widely; if you do not have adequate knowledge and experience to use this instruction sheet and safely accomplish the tasks described, please hire a professional to assist you for your safety and the safely of your vehicle and others.

#### Limitation of Liability

Except as required by Applicable Law, LMR, its affiliates, officers, directors, employees and agents will not be responsible for any loss of profits, revenues, business opportunities, goodwill, or anticipated savings, indirect or consequential loss, punitive damages caused by:

Errors, mistakes, or inaccuracies in this instruction sheet

Personal injury or property damage resulting from your use of this instruction sheet

This limitation of liability provision applies to any claim regardless of whether the claim asserted is based on warranty, contract, tort or any other legal theory.

Use this information at your own risk. Any injury, damage, or loss that may result from use of the tools, equipment, products, or information contained in this instruction sheet is the sole responsibility of the user.

#### Indemnity

To the extent permitted by Applicable Law, you agree to defend, indemnify and hold harmless LMR, its Affiliates, officers, directors, employees, agents, information providers, licensors, and other partners from and against any and all claims, damages, obligations, losses, liabilities, costs or debt, and expenses (including but not limited to attorney's fees) arising from: (i) your use of and access to this instruction sheet; (ii) your violation of any term of the Agreement; (iii) your violation of any third party right, including without limitation any copyright, property, or privacy right; or (iv) any claim that your actions caused damage to LMR or a third party. The defense and indemnification obligations will survive this Agreement and your use of this instruction sheet.

