



## Fox Mustang Front Lighting Harness Installation Instructions



\*product may appear different from product received

These Instructions Cover the Following Part Numbers:

FH-073	1989 Ford Mustang Lighting Harness
FH-075	1990 Ford Mustang Front Lighting Harness
FH-083	1991-1993 Ford Mustang Front Lighting Harness

### Installation Instructions:


- 1) Disconnect battery
- 2) Remove factory harness, taking note how wires are run. Disconnect main black 8 way connector at driver's side, near the brake master cylinder.
- 4) Install replacement harness following factory routing, starting at the main black 8 way connector at driver's side, near brake master cylinder. At the ground ring terminals that mount on the radiator support, make sure ground has clean metal and will make good contact to chassis metal.

- 5) If your car was equipped with fog/driving lights, or you have added fog/driving lights, the 2 way connectors with orange and black wires are for this function. We have supplied the other half of the connector as well as terminals and seals to mate to these connectors. If you have factory fog/driving lights, you will need to remove the factory connector and use the seals/terminals/connector supplied. Follow these directions for terminal crimping:

- A) Strip wire roughly 1/4 inch.  
B) Install green seal making sure not to fray any wire stands:




- C) Crimp terminal onto wire, crimping the wire strand area first. Crimp the wire seal second. If you do not have the proper crimp tool, use pliers to fold the flaps onto the wire. The cable seal flaps only need enough crimp to provide friction to keep the seal in place



- D) Install completed wires/terminals into connector sockets.

Once all wires/terminals are installed close secondary lock.



- 6) Complete installation by confirming harness is routed away from exhaust and any moving parts.

Wire Works Enterprises Inc  
T/A Ron Francis Wiring  
200 Keystone Rd.  
Chester, PA 19013  
800-292-1940  
www.ronfrancis.com

### Warranty Information

All Ron Francis Wiring products are warranted for 1 year from purchase date. There are no other representations, warranties or conditions expressed or implied, statutory or otherwise except those herein contained. Warranty does not cover any defect which is the result of improper installation or modification of the system or any of its components by purchaser.

Ron Francis Wiring, its dealers or agents will not be liable, in any way, for any damage, loss, injury or other claims, resulting from the use or misuse, or inability to use any of our products. Purchaser and/or user, assumes liability of any kind connected with the use and/or application of our products. Copyright © 2006 Ron Francis Wiring