



**1982-04 MUSTANG ADJUSTABLE  
CLUTCH CABLE KIT  
INSTALLATION INSTRUCTIONS**

Prop. 65 Warning for California Residents  
WARNING: This product may contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

**Instructions**

1. Support the vehicle on a lift or jack stands.
2. Loosen the clutch fork dust cover bolt with a 5/16" socket and remove the cover. Using a pry bar, move the clutch fork forward. **(Figure A)** This will allow you to slip the end of the factory clutch cable out the large hole in the fork.
3. Remove the clutch cable retaining clip then remove the cable from the bellhousing.
4. Locate the clutch cable bracket and remove from the frame rail with a 3/8" socket.
5. Locate the factory plastic quadrant just above the gas pedal. **(Figure B)** Pull the end of the cable over the fangs of the quadrant, then remove the cotter pin from the quadrant shaft. Next, remove the spring and factory quadrant from the shaft.
6. Remove the cotter pin from the self-adjusting gear by flipping the spring over the arm, then slide the gear off the quadrant shaft. **(Figure C)**
7. With your hood open, unbolt the head of the clutch cable from the firewall with a 5/16" socket. Remove the factory clutch cable from the vehicle.
8. Before installing the new clutch cable, file down the four small tabs on the head of the

