



Camber Caster Plates 2011-2014 Ford Mustang All Excludes GT500

Camber & Caster plate assemblies for the 2011-2014 Ford Mustangs. This Camber/Caster kit comes complete and READY to bolt in right out of the box. (no need to swap anything over from the factory mount). Whether you are using the car for street, autocross, road racing or drag racing these plates are designed for you. These plates have an offset design allowing for you to install them in the street orientation or a race orientation allowing for the most camber adjustment available compared to any other plate on the market.

- **Note: These Caster/Camber plates are side specific.**

DRIVER SIDE



PASSENGER SIDE



Recommended Tools

- Assorted Basic Hand Tools
- Floor Jack & (2) Jack Stands
- 1/2" Torque Wrench
- Spring Compressor



FIND YOUR NEXT MOD! **FAST, FREE SHIPPING ON \$49+ ORDERS!**

Tools needed:

ratchet
10mm, 13mm, 17mm, 18mm, 19mm, 21mm
sockets 10mm & 21mm wrenches
torque wrench
jack
jack stands
spring compressor
trim panel tool

Camber/Caster Plate Installation Sheet:

1. Raise the vehicle to adequate working height and properly support the vehicle using proper jack stands (not a jack), then remove the wheels. If you have a strut tower brace, remove that as well. Re-install the nuts on the strut after you remove the brace. Remove the 10mm bolt that holds the brake line to the strut. Next, remove the wiring harness that is clipped to the strut. Use the trim panel tool to remove the wiring clip.



2. Remove the 18mm nut on the strut for the sway bar end link. Remove the end link from the strut by pushing it through the hole. Do Not Use Impact Gun



3. Support the rotor with a jack stand, jack, or and then remove the two 18mm bolts that attach the strut to the knuckle. After the nuts are removed, you may need to wiggle the strut back and forth to be able to slide the bolts out of the knuckle. Once the bolts are removed, you will see why a jack stand was needed to support the rotor and knuckle assembly. If not properly supported, damage to the brake lines, wiring, or ball joints could occur. If you prefer you can carefully remove the spindle to strut bolts and carefully remove them while support the rotor by hand. Once they are removed you will want to safety tie the spindle/rotor assembly to the anti-roll bar to make sure the brake line does not get damaged.



4. With everything under the car loosened, you can now remove the 4 nuts in the engine bay. Once these 4 nuts are removed, the strut will come right out, so be sure to hold the strut while removing the fasteners.



5. With the strut removed, you can now compress the spring with the spring compressor. Many auto parts stores have a tool rental program if you don't have your own. Usually, you leave a deposit for the tool, and get 100% back when you return the tools to the store. Install one compressor on each side of the spring, and engage the safety pins. Next you can start to compress the spring, compressing both sides evenly. Take your time and do a little bit on each side until the spring is compressed.



6. The spring is compressed enough when the spring has no pressure on the upper mounting plate, as shown to the right.



7. Once the spring is compressed, remove the 21mm nut on the top of the strut. You may need to hold the strut shaft with a 10 mm wrench to prevent it from spinning. Once the nut is removed, remove the upper strut mount. We do NOT recommend using impact guns on struts or shocks.



THESE CAMBER/CASTER PLATES ARE SIDE SPECIFIC!

8. Place the camber plate assembly with the spring seat over the strut shaft like shown. Strut not shown for clarity. NOTE: OUR NEW DESIGN DOES NOT HAVE THE SPRING LOCATOR AS THE SPRING IS LOCATED OFF THE STRUT.



9. Re-Install the strut nut and torque to factory specifications. Spring not shown. (Do Not Use Impact Guns).



THESE CAMBER/CASTER PLATES ARE SIDE SPECIFIC!

DRIVER SIDE



PASSENGER SIDE



10. Once the strut nuts have been torqued you can now remove the spring compressor. Carefully remove it and make sure the springs are seated properly in the indexed area of the strut and camber plate spring seats.

11. The bottom of the strut tower must be smooth and free from any raised metal or flash. Run your finger across the underside of the tower and make sure it is smooth and free from scratches. If it is not smooth file or sand down any rough spots.



12. The camber plate has an offset bearing design which allows you to install them in a street setting or a race setting. To install in the street setting which will allow you to more positive camber for lowered cars simply install with the bump toward the inside of the car (engine side) and the race setting you will install the bump toward the fender (outside) of the car.

STREET RECOMMENDATIONS:

If you are looking for a factory alignment setting and you are 1" or more lowered we recommend using the street setting/orientation. If you are looking for a factory alignment setting and you are 1" or less lowered we recommend using the race setting/orientation.

ROAD RACE RECOMMENDATIONS:

Depending on the type of racing you are doing will determine how much camber you want. Typically road racing and auto cross will need more negative camber. If you are setting your car up for this we recommend using the race orientation.



13. We install one 8mm nut onto one of the studs to keep the caster plate in place during shipping. **Make sure to remove this nut before trying to install the assembly into the car.**

14. Carefully reinstall the strut assembly into the vehicle using the desired orientation from step # 18 and install the supplied 8mm washers and 8mm locking nuts. Do not tighten.



15. Install the supplied M10 x 20mm bolt with 10MM support washer into the caster slot in the factory tower. You can now snug all 5 mounting bolts and nuts.



16. Reattach the spindle to the strut and torque the bolts to the factory setting of 148 lb-ft.

Note: Ford recommends replacing these bolts every time you remove them. You can purchase these from your local Ford dealer.

17. Reattach the ABS sensor wire and brake line bracket and torque to Ford specifications of 15 lb-ft.

18. Reattach the sway bar end link and torque to factory specifications of 85 lb-ft. Do not use an impact gun.

19. With the tires still off the ground slide the strut all the way forward toward the front of the car. You can now tighten the M10 bolt to 26 lb/ft.

20. We recommend centering your strut shaft in the center of the strut tower opening to get you to the alignment shop. Once you have centered the strut you can torque the 8mm locking nuts to **17 lb-ft. or 204 lb-INCH..**

21. Repeat the steps for the other side.

22. Install the wheels and safely lower the vehicle off the jack stands to the ground. Make sure you torque your wheels to the factory torque specifications.

23. Align your vehicle to your desired alignment specifications or factory specifications if you are happy with them. Caster should be set first.

Alignment Notes:

You will not be able to adjust these plates with the vehicle on the ground or the suspension loaded. The front must be raised in order to adjust the camber/caster plate. Due to the anti-roll bar loading it may be required to lift both front tires off the ground to make adjustments.

These SVE camber/caster plates have separate adjustments for camber and caster. You must adjust caster first and lock down the M10 caster bolt to 26 lb-ft and then adjust camber.

Caster Adjustment



Camber Adjustment



FIND YOUR NEXT MOD! **FAST, FREE SHIPPING ON \$49+ ORDERS!**